## **Specifications**

•	
	LBC-24W
	Concrete Curber
Dimensions Length	12′ 6″ (3.81 m)
Width	8' 0" (without mold) (2.44 m) 8' 6" (with sensor) (2.59 m)
Height Weight	4'3" (1.29 m) 7,500 lbs. (3,402 kg)
Engine	
Make Performance	Kubota Tier 3 Diesel Engine 44 HP (32.8 kw)
Controls	Top-Con electronic control systems
Vibration	(2) Minnich (up to 10,000 VPM)
Pour Performance  Mold Width  Mold Height  Minimum Radius  Minimum Clearance  Grading Width	Maximim 48" (1.2 m) Maximum 24" (.61 m) 24" (.61 m) 2" (5.1 cm) 5' (1.5 m)
Transmission	Hydrostatic
Tires	26x12x12 (Silicone Filled)
Capacities Fuel Hydraulic	20 gal (75.7 l) 30 gal (113.6 l)
Options	Third Vibrator Vector Thrust Cylinder



**Operator's Control Panel** 

Front and rear operator control stations provide fingertip control of applications.

Operator controls engine speed, vibration, automatic steering, hopper raise and lower, grading



**Front Controls** 

blade and auger control. Master switch provides for smooth and easy automatic restart. Equipped with two auxiliary ports for hydraulic attachments.

LeeBoy makes continuous improvements in all its products. We reserve the right to change specifications without notice. Photos and illustrations may contain standard and optional equipment.

LBC-24W - 05-08- 5K #11703



🙎 VT LeeBoy

# LeeBoy has designed and manufactured superior asphalt paving and grading products since 1964. The LeeBoy brand is well-known for its quality and innovative design. This standard of quality provides contractors with dependable, low maintenance equipment with a high resale value.

"LeeBoy is dedicated to providing top quality parts and service support on every unit sold."

#### Other Members of the LeeBoy Family of Products...







7000 Asphalt Paver

420 Pneumatic Roller

685B Motor Grader

Contact your LeeBoy dealer:



## **Concrete Curber Series**

## LBC-24W



### **Quality Curbing Made Easy With The LBC-24W**

The **LeeBoy LBC-24W** Concrete Curb and Gutter machine is a maneuverable, compact machine that enhances jobsite productivity, speed and quality. The **LBC-24W** is designed to cost-effectively slipform curbs and gutters, alley ribbons and narrow sidewalks. Steering controls turn a smooth radius as tight as 24 inches eliminating time-consuming hand forming.

The **LBC-24W** features a powerful 44-HP Tier 3 turbo diesel engine, hydrostatic variable speed drive, superior visibility and electronic controls, enabling a one person operation. Its compact size (7,500 pounds), all-wheel drive and maneuverability make for simple set up and transport.

**LBC-24W** can be used on soil or pavement using a stringline or manual controls. Pouring molds can be replaced quickly and easily with the quick-change mold system.

#### LBC-24W Concrete Curb and Gutter Machine

#### **Featured With:**

- 44-HP Tier 3 Turbo Diesel Engine
- Narrow Sidewalks
- 24-Inch Radius with Vector Thrust Cylinder Option
- Grades On Line
- Auto Steering

- Patent Pending Articulating Mold Design
- Below Grade Pours (Option)
- 7,500 Pound Weight
- All-Wheel Drive
- Cuts Driveway Depression (Option)